
IDEAL electrical	**WIRE-TWIST™** WIRE CONNECTORS	**MODELS** **WT1, WT2, WT3, WT4, WT6**

FEATURES/BENEFITS:



- POSITIVE GRIP SHELL DESIGN FOR FAST, EASY INSTALLATION
- FIXED, SQUARE-WIRE SPRING CREATES SECURE CONNECTIONS
- DEEP SKIRT PROTECTS AGAINST FLASH-OVER

ELECTRICAL:

VOLTAGE: WT1/WT2 300 VOLTS MAX.
WT3/WT4/WT6 600 VOLTS MAX.*

(* 1,000 VOLTS MAX. SIGNS & FIXTURES)

APPLICATION TOOLS:

- ACAM (AUTOMATIC CONNECTOR APPLICATION MACHINE)
- WIRE-NUT® Wire Connector Sockets: **30-903** (WT1 & WT2), **30-904** (WT3), **30-906** (WT4 & WT6), **H-632** (WT3, WT4, & WT6), **30-902** (WT3, WT4, & WT6)

PHYSICAL:

HOUSING: POLYPROPYLENE (UL 94V-2 FLAME RATED)
INSERT: STEEL
PLATING: ZINC

STANDARDS & SPECIFICATIONS:


UL LISTED: UL 486C
CSA CERTIFIED: C22.2 NO. 188
RoHS COMPLIANT

WIRE RANGE & COMBINATIONS:

- Solid and/or stranded wire combinations unless stated otherwise
- Consult website for other combinations not listed

MODEL	WT1 (GRAY)	WT2 (BLUE)	WT3 (ORANGE)	WT4 (YELLOW)	WT6 (RED)
WIRE STRIP LENGTH	Solid: 1/4" (6 mm) Str: 5/16" (8 mm)	≤ #16 AWG: 1/2" (13 mm) All Others: 3/8" (9.5 mm)	≤ #16 AWG: 3/8" (9.5 mm) All Others: 5/16" (8 mm)	≤ #16 AWG: 7/16" (11 mm) All Others: 3/8" (9.5 mm)	≤ #16 AWG: 1/2" (13 mm) All Others: 7/16" (11 mm)
COMBINATIONS: - Listed as a Pressure-Type wire connector for use on the following solid and/or stranded Cu/Cu wire combinations. - Consult IDEAL for a complete list of all UL Listed wire combinations.	300V MAX: 1 #14 1 or 2 #16 2 to 3 #18 2 to 4 #20 3 to 4 #22 5 #22 Sol.	300V MAX: 2 to 3 #16 2 to 4 #18 3 to 5 #20 3 #18 w/ 1 to 2 #20 or #22 4 #20 w/1 #22	300V MAX: 5 #18 5 #22 3 to 4 #16 4 to 5 #20 600V MAX:* 2 #16 2 to 4 #18	300V MAX: 2 #10 3 #12 5 #16 5 #18 600V MAX:* 1 #8 1 #10 1 to 2 #12 1 to 3 #14 2 to 5 #16 2 to 6 #18	300V MAX: 3 #10 5 #12 600V MAX:* 1 #6 or #8 1 to 2 #10 1 to 4 #12 2 to 5 #14 4 to 6 #16

DIMENSIONS:



	A		B	
MODEL	INCHES	mm	INCHES	mm
WT1	0.61	15.4	0.34	8.5
WT2	0.70	17.8	0.39	9.9
WT3	0.89	22.6	0.45	11.4
WT4	1.01	25.6	0.54	13.7
WT6	1.11	28.2	0.64	16.2

ORDERING INFO:

CATALOG

WT1 (GRAY)		WT2 (BLUE)		WT3 (ORANGE)		WT4 (YELLOW)		WT6 (RED)	
WT1-1	Box of 100	**WT2-1**	Box of 100	**WT3-1**	Box of 100	**WT4-1**	Box of 100	**WT6-1**	Box of 100
WT1-B	Bag of 500	**WT2-B**	Bag of 500	**WT3-B**	Bag of 500	**WT4-B**	Bag of 500	**WT6-B**	Bag of 250
		WT2-SK	Barrel of 1,000	**WT3-SK**	Barrel of 50,000	**WT4-SK**	Barrel of 25,000	**WT6-SK**	Barrel of 25,000

FACTORY CONTACT:

IDEAL INDUSTRIES, INC.
1375 PARK AVENUE, SYCAMORE, IL, 60178

P: (800) 324-9571
F: (888) 222-6140
E: oem@idealindustries.com

NOTES: